

1700 Division Street, New London, WI 54961

Phone: (920) 982-4030; Fax: (920) 982-6800

Website: www.nleco.com

This shallow frame, large drive pulley (8" Diameter) conveyor is versatile enough to get into tight spaces and durable enough for applications up to 36" wide and 100' long. It is built for low maintenance operation in medium duty production, assembly and packaging operations.

Widths: Up to 36"

Lengths: 5' - 100' (6" Increments)

Standard Length is 5', Two Piece Bolt Together

Standard Speed: 60 FPM

Standard Motor: 1/2 HP 230/460/3/60 TEFC

Standard Drive: Bottom Mount, Right Side

Standard Belt: Black PVC 120, Clipper Lacing

Drive Pulley: 8" Dia Crown Face Rubber Lagged x 1-7/16"

Infeed Pulley: 4" Dia Crown Face Take Up x 1-3/16"

Frame: 2 3/4" Deep x 12 Gauge

Bearings: Grease Sealed

Standard Supports: 30" Elevation Top of Belt

UpTime Express – Widths shaded in blue are available to ship in 24 hours

BELT WIDTH:	8"	10"	12"	14"	16"	18"	20"	24"	30"	36"
FRAME WIDTH:	11"	15"	15"	21 1/2"	21 1/2"	21 1/2"	28"	28"	34"	40"

