

1700 Division Street, New London, WI 54961

Phone: (920) 982-4030; Fax: (920) 982-6800

Website: www.nleco.com

MEDIUM DUTY FLOOR-TO-FLOOR CONVEYOR

A medium-duty inclined conveyor built for moving narrower and lighter items up shorter levels. It features a space-saving shallow frame and a double nose-over discharge that provides smooth incline to horizontal transition.

***Power Feeder is Optional**

Widths: Up to 30"

Lengths: 5'-40' (6" Increments)

Standard Speed: 60 FPM

Standard Motor: 1/3 HP 230/460/3/60 TEFC

Standard Drive: Bottom Mount, Right Side

Standard Belt: Black Rubber Rough Top, Clipper Lacing

Drive Pulley: 4" Dia Crown Face Rubber Lagged x 1-3/16"

Infeed Pulley: 4" Dia Crown Face Take Up x 1-3/16"

Infeed Frame: 2 3/4" Deep x 12 Gauge

Drive Frame: " Deep x 12 Gauge

Bearings: Grease Sealed

Standard Supports: 30" Elevation Top of Belt

Standard Nose-Over: Adjustable Double Nose-Over

BELT WIDTH:	8"	10"	12"	14"	16"	18"	20"	24"	30"	36"
FRAME WIDTH:	11"	15"	15"	21 1/2"	21 1/2"	21 1/2"	28"	28"	34"	40"

