

TAPERED INFEED 2 1/2" PITCH HINGED STEEL BELT

1700 Division Street, New London, WI 54961

Phone: (920) 982-4030; Fax: (920) 982-6800

Website: www.nleco.com

This units infeed tapers from 6 5/8" to 4 1/8" and then back to 6 5/8" at the incline. The very shallow 4 1/8" section is designed so the unit can fit into a very tight space inside or under an existing machine.

Widths: 6", 8", 12", 18", 24", 30" and 36"
(Custom Widths Available)

Lengths: Per Application

Standard Speed: 30 FPM

Standard Motor: 1/2 HP 230/460/3/60 TEFC

Standard Drive: Top Mount, Right Side

Frame: 6 5/8" Deep x Formed 12 Gauge

Drive Shaft: 1 3/16" diameter

Bearings: Grease Sealed

Sprockets: 5 Tooth x 4.25" Pitch Diameter

Infeed: The standard infeed is semi-rounded as shown below.

Belt: 2 1/2" Pitch Hinged Steel Belt, One Piece Apron, with 5/8" high cleats on 12 1/2" Centers, 1.5" high side wings, 1.5" Diameter Rollers (Flanged Rollers are available), Outside Sidebars are required on belts greater than 18", but also optional for smaller widths.

BELT WIDTH:	6"	8"	12"	18"	24"	30"	36"
FRAME WIDTH:	10"	12"	16"	22"	28"	34"	40"

