

HEAVY DRIVE & INFEED SHAFT Model 220 HEAVY DUTY SLIDER BED

1700 Division Street, New London, WI 54961

Phone: (920) 982-4030; Fax: (920) 982-6800

Website: www.nleco.com

This heavy duty, deep frame slider bed built for low maintenance and extended use in virtually any manufacturing environment. This sturdy, solid conveyor is designed for longer, wider and heavier weight slider bed applications.

Widths: Up to 48"

Lengths: 5' - 100' (6" Increments)

Standard Length is 5', Two Piece Bolt Together

Standard Speed: 60 FPM

Standard Motor: 1/2 HP 230/460/3/60 TEFC

Standard Drive: Bottom Mount, Right Side

Standard Belt: Black PVC 120, Unibar Lacing

Drive Pulley: 8" Dia Crown Face Rubber Lagged x 1-11/16"

Infeed Pulley: 4" Dia Crown Face Take Up x 1-7/16"

Frame: 5 1/2" Deep x 12 Gauge

Standard Supports: 30" Elevation Top of Belt

| BELT WIDTH: | 8" | 10" | 12" | 14" | 16" | 18" | 20" | 24" | 30" | 36" | 42" | 48" |
|--------------|-----|-----|-----|---------|---------|---------|-----|-----|-----|-----|-----|-----|
| FRAME WIDTH: | 11" | 15" | 15" | 21 1/2" | 21 1/2" | 21 1/2" | 28" | 28" | 34" | 40" | 46" | 52" |

