

STANDARD DUTY V-GUIDED CLEATED INCLINE CONVEYOR (V-GUIDED MODEL 500)

This light weight shallow frame parts conveyor provides the flexibility to be used in both horizontal and inclined applications. The V-guided system keeps the belt centered for use in side loading and wide applications. This unit includes a cleated belt and siderails making it the right choice for narrow, shorter run, inclined V-guided applications.

Widths: 4" – 24"

Lengths: Up to 20' (6" Increments)

Standard Length is 4', Two Piece Bolt Together

Standard Speed: 60 FPM

Standard Motor: 1/3 HP 230/460/3/60 TEFC

Standard Drive: Top Mount, Right Side

Standard Belt: Black PVC 120 with 1 1/2" high cleats on 12" centers, Clipper Lacing

Drive Pulley: 4" Dia Flat Face Rubber Lagged x 1-3/16"

A Section "V" Guided

Infeed Pulley: 4" Dia Crown Face Take Up x 1-3/16" A Section "V" Guided

Infeed Frame: 6-5/8" Deep x 12 Gauge

Drive Frame: 6-5/8" Deep x 12 Gauge

Others: Base unit includes 3 1/2" high Side rails and a Bottom pan

BELT WIDTH:	4"	8"	12"	18"	24"	30"	
FRAME WIDTH:	7"	11"	15"	21 1/2"	28"	34"	

