

LOW PROFILE INFEEED 2 1/2" PITCH CHIP CONVEYOR

1700 Division Street, New London, WI 54961
Phone: (920) 982-4030; Fax: (920) 982-6800
Website: www.nleco.com

This unit features a very shallow infeed combined with the strength of a deeper intermediate and drive frame. The shallow 5 3/8" deep infeed is designed to fit under an existing machine. The remainder of the unit is 6 5/8" deep. This unique combination provides both strength and space flexibility.

Widths: 6", 8", 12", 18", 24", 30" and 36"
(Custom Widths Available)

Lengths: Per Application

Standard Speed: 30 FPM

Standard Motor: 1/2 HP 230/460/3/60 TEFC

Standard Drive: Top Mount, Right Side

Bearings: Grease Sealed, Marine @ Infeed

Infeed Frame: 5 3/8" Deep x Formed 12 Gauge

Intermediate Frame: 6 5/8" Deep x Formed 12 Gauge

Sprockets: 5 Tooth x 4.25" Pitch Diameter

Belt: 2 1/2" Pitch Hinged Steel Belt, One Piece Apron, with 5/8" high cleats on 12 1/2" Centers, 1.5" high side wings, 1.5" Diameter Rollers (Flanged Rollers are not available), Radial Sidewings, Outside Sidebars are required on belts greater than 18" wide.

BELT WIDTH:	6"	8"	12"	18"	24"	30"	36"
FRAME WIDTH:	10"	12"	16"	22"	28"	34"	40"

