

MODEL 760

6" PITCH HINGED STEEL BELT CONVEYOR

1700 Division Street, New London, WI 54961 Phone: (920) 982-4030; Fax: (920) 982-6800

Website: www.nleco.com

A very rugged, heavy duty hinged steel belt conveyor. Designed for use in heavy duty industrial steel and scrap applications.

Frame Depth: 21 3/4"

Frame Width: Belt Width + 11 1/4"

Bearings: Grease Sealed

Sprockets: 6 Tooth x 12" Pitch Diameter

Belt: 6" Pitch Hinged Steel Belt with 4" High cleats on 48" Centers, 7 Gauge x 4" high side wings, 3" diameter

x 1.5" flanged rollers, Outside Sidebars

Supports: Structural "C" Channel; 6" x 8.2#

Others: Access panels, Take Up at Infeed, 16" High 7

gauge Siderails

Widths: 12" – 72"

(Custom Widths Available)

Lengths: Depends on Application (Min. of 8');

Standard Infeed=60" (Min. of 36")

Standard Discharge=60"

Standard Speed: 30 FPM

Standard Motor: 3 HP 230/460/3/60 TEFC

Standard Drive: Top Mount, Right Side

Frame: Structural "C" Channel 3" x 4.1#; (7 Gauge

also Available);

BELT WIDTH:	12"	18"	24"	30"	36"	48"	60"	72"
FRAME WIDTH:	23 ¼"	29 1/4"	35 1/4"	41 1/4"	47 1/4"	59 1/4"	71 ¼"	83 1/4"



