



**Uptime
Express™**

Quick Shipment Program



TOUGHTRAK™ 48-HOUR AND 10-DAY SHIPMENT LIST

- Belt Widths of 4", 6", 8", 10", 12", 18", and 24"; Lengths from 2' – 10'*
- Fixed Speeds of 30, 45, and 60 FPM; Variable Speeds from 1.5 – 60 FPM
- 2-Ply Black PVC 70 and Green Urethane
- In NLE Blue or Hammertone

Option Category	Description	Model 150	Model 250
Back Rail	Back Rail w/1", 2", and 3-1/2" Vertical Rails	●	●
Belt Scraper	Belt Scraper	●	●
Bottom Pan	Bolt-On Bottom Pan	■	■
	Stainless Steel Bottom Pan	●	●
Casters	3-1/4" Rigid and Swivel Casters Only	■	■
Drive Location	Bottom Mount, Top Mount, and Side Mount	■	■
	Center Drive w/Bottom or Side Mount	■	■
	Shaft Mount (150 Only)	■	●
Fixed End Stop	Fixed End Stop or Nose Bar Transfer	●	●
Rollers	Precision Snub Rollers (Standard)	■	■
Side Rails	Vertical Rails in 1", 2", and 3-1/2"	■	■
	Flared Rails at 45° in 1" and 2"	●	●
	Adjustable – Double and Single Bar	●	●
Supports	2"–73" Height in Compact and Standard Duty	■	■
	Compact (A thru 0G-2), Standard (1A thru 2G-2)	■	■
Special Paint	All Other NLE Stock Colors – 10-Day	●	●

Express program is after receipt of approved drawing. Changes may disqualify express shipment.

* Lengths available in 6" increments.

■ = 48-Hour

● = 10-Day

SLIDER BED 24-HOUR AND 10-DAY SHIPMENT LIST

- 200, 210, and 410 in 4", 6", 8", 10", 12", 18", 24", and 30" Widths; 5' – 40' Lengths (24-Hour) and 41' – 100' (10-Day)*
- 220 and 420 in 6", 8", 10", 12", 18", 24", 30", and 36" Widths; 5' – 40' Lengths (24-Hour) and 41' – 100' (10-Day)*
- Fixed speeds of 30, 45, 60, 90, and 120 FPM; Variable speeds from 1.5 – 120 FPM
- 2-Ply Black PVC 120 (4" – 36"), 2-Ply Black RRT (8" – 30"), Green Urethane (4" – 24") Belts, All 24-Hour
- In NLE Blue

Option Category	Description	Model 200	Model 210	Model 220	Model 410	Model 420
Belt Scraper	Belt Scraper	●	●	●	●	●
Bottom Pan	Bolt-On Bottom Pan	■	■	■	■	■
	UHMW Lined or Stainless Steel Bottom Pan	●	●	●	●	●
Brush	Fixed Brush at Discharge	●	●	●	●	●
Casters	3-1/4", 4", and 6" Swivel and Rigid Casters	■	■	■	■	■
Ceiling Hangers	Ceiling Hanger Brackets	●	●	●	●	●
Drive Location	Bottom Mount and Top Mount	■	■	■	■	■
	Shaft Mount	●	●	●	●	●
	Center Frame – Center Bottom-Side	■	■	■	■	■
End Plate	Vertical for 3-1/2" and 6" Side Rails	●	●	●	●	●
Pulley Guard	Pulley Guard at Infeed	●	●	●	●	●
Rollers	Precision Return and Snub Rollers	●	●	●	●	●
Roller Stop	Roller Stop at Drive	●	●	●	●	●
Side Rails	Vertical Rails in 1-1/2", 3-1/2"	■	■	■	■	■
	Vertical Rails in 1-1/2", 3-1/2", 6", and 12" Inc UHMW Lined	●	●	●	●	●
	Vertical Rails w/Skirting 3-1/2" and 6"	●	●	●	●	●
	Flared Rails at 45° in 3-1/2" and 6"	●	●	●	●	●
	Troughed 3-1/2"	■	■	■	N/A	N/A
	Adjustable – Double and Single Bar	●	●	●	●	●
Top Cover	Vertical Side Rail Top Cover	●	●	●	●	●
Transfer Roller	Transfer Roller at Drive and Infeed	■	■	■	■	■
Work Leaves	Work Leaves in 7", 11", 15", and 21-1/2" Wide	●	●	●	●	●
Supports	2" – 73" Height, Standard, and Medium Duty	■	■	■	■	■
	Standard (1A thru 2G-2), and Medium (3A thru 3L)	■	■	■	■	■
	All Other Supports	●	●	●	●	●
Special Paint	All Other NLE Stock Colors – 10-Day	●	●	●	●	●

Express program is after receipt of approved drawing. Changes may disqualify express shipment.

* Lengths available in 6" increments.

■ = 24-Hour

● = 10-Day

500 24-HOUR AND 10-DAY SHIPMENT LIST

- Belt Widths of 6", 8", 12", 18", and 24"; Lengths from 4' – 25'*
- Fixed Speeds of 30, 45, 60, 90, and 120 FPM; Variable Speeds from 1.5 – 120 FPM
- Black PVC 120, 1-1/2" Cleats x 12" Centers
- In NLE Blue

Option Category	Description	Model 500
Bottom Pan	Bolt-On Bottom Pan	■
	Stainless Steel Bottom Pan	■
Casters	4", and 6" Swivel and Rigid Casters	■
Ceiling Hangers	Ceiling Hanger Brackets	●
Chutes	Discharge Chute at Drive	■
Drive Location	Top Mount and 45°	■
	Side Mount and Shaft Mount	●
Hoppers	Flared 6"	■
	Straight Side	●
Pulley Guard	Pulley Guard at Infeed	●
Side Rails	Vertical Rails in 1-1/2", 3-1/2", and 6"	■
	Vertical Rails in 12"	●
	Vertical Rails in 1-1/2", 3-1/2", 6", and 12" Inc UHMW Lined	●
	Vertical Rails w/Skirting 3-1/2" and 6"	●
	Troughed 3-1/2"	●
Top Cover	Vertical Side Rail Top Cover	●
Supports	2" – 73" Height in Standard and Medium Duty	■
	Standard (1A thru 2G-2) and Medium (3A thru 3L)	■
	Heavy Duty Supports	●
Special Paint	All Other NLE Stock Colors – 10-Day	●

Express program is after receipt of approved drawing. Changes may disqualify express shipment.

* Lengths available in 6" increments.

■ = 24-Hour
● = 10-Day

STEELTRAK™ 3-5 DAY AND 10-DAY SHIPMENT LIST

- Belt Widths of 6", 8", 12", 18", and 24"; Overall Horizontal Lengths of 35' (3–5 Day) and 50' (10-Day)*
- Fixed Speeds of 30, 45, and 60 FPM; Variable Speeds from 1.5–60 FPM
- Curves of 30°, 45°, and 60°; Welded Construction Only
- All 3–5 Day are NLE Blue or Hammertone

Option Category	Description	Model 721	Model 722	Model 724	Model 726	Model 727
Bars	Heat Dissipating Bars, Impact Bars Welded to Aprons (Bottom and Top)	●	●	●	●	●
Back Rail	All Standard Rails (2", 3-1/2", and 6")	■	■	●	●	
Bottom Pan-Bolt On	Bolt-On Bottom Pans	■	■	●	●	●
Bottom Pan-Liquid Tight	Liquid Tight Bottom Pans	●	●	●	●	●
Brush	Fixed Brush at Discharge and Heavy Duty Brush at Discharge	■	■	●	●	●
Cleats	1-3/8" w/Conventional Belts and 1-1/8" High w/Flattop Belt	■		●		
	7/8" High w/Conventional Belt and 5/8" w/Flattop Belts		●		●	●
Casters (Steel)	4" and 6" Rigid and Swivel	■	■	●	●	●
Ceiling Hangers	Ceiling Hanger Brackets	●	●	●	●	●
Chip Suppressor	Chip Suppressor	■	■	●	●	●
Drain Holes and Plugs	Drain Holes and Drain Plugs at Infeed	●	●	●	●	●
Drive Location	Top Mount, Side Mount, and 45° Top Mount	■	■	●	●	●
Flanged Rollers	Standard	■	■	●	●	●
Impact Rail	Impact Rails w/Channel Welded to Frame	■	■	●	●	●
Key Stock	Key Stock Over Side Wings	●	●	●	●	●
Lifting Lugs	Location Must be Specified	■	■	●	●	●
Marine Bearings	Marine Bearings w/Bolt-On Bottom Pan	●	●	●	●	●
Outside Sidebars	Outside Sidebars	■	■	●	●	●
Radial Sidewings	720-721 are 1-1/2" High	■	■	●	●	●
	722, 725, and 727 are 1" High					
Side Rails	Flared 45° (2", 3-1/2", and 6")	■	■	●	●	●
	Vertical (2", 3-1/2", and 6")	■	■	●	●	●
	Vertical (12") Side Mount Drive	●	●	●	●	●
Special Paint	All Other NLE Stock Colors –10-Day	●	●	●	●	●
Take Up	Take Up at Infeed	●		●		
Top Cover	Top Cover for Vertical Rails (2", 3-1/2", and 6") 12" – 10-Day	■	■	●	●	●
Wiper Cleat	Wiper Cleat	●	●	●	●	●

Express program is after receipt of approved drawing. Changes may disqualify express shipment.

* Lengths available in 6" increments.

■ = 3-5 Day

● = 10-Day

DIEBEL 5-DAY EXPRESS SHIPPING PROGRAM

Option Category	Description	Model D-1300	Model D-2300	Model D-3300
Specifications	Weight Capacity	40 lbs	80 lbs	200 lbs
	Length	1' – 20'	18" – 20'	18" – 20'
	Belt Width	2", 4", 6", 8", 12", 18"	1", 2", 4", 6", 8", 12", 18"	2", 4", 6", 8", 12", 18"
Drive	Drive Locations	End Drive and Center Drive	End Drive and Center Drive	End Drive and Center Drive
	Infeed Pulley Diameter	1.125"	2.48"	2.48"
	Drive Shaft Diameter	5/8"	5/8"	3/4"
	Infeed Frame Depth	1.125"	2.48"	2.48"
Motor*	Single Phase 110/115 VAC Gear Motor	29, 43, 59, 88 End, 85 Center	29, 43, 59, 88 End, 85 Center	N/A
	3 Phase 200/220/230 VAC Gear Motor	29, 43, 59, 88 End, 85 Center	29, 43, 59, 88 End, 85 Center	N/A
	Single Phase 115/230/1/60 Motor/Reducer (56C)	N/A	N/A	29, 45, 58, 89
	3 Phase 230/460/3/60 Motor/Reducer (56C)	N/A	N/A	29, 45, 58, 89
Frame	Box Beam Construction	N/A	1", 2", 4", 6" BW	2", 4", 6" BW
	Plate and Rail Construction	2", 4", 6", 8", 12", 18" BW	8", 12", 18" BW	8", 12", 18" BW
Belt	2-Ply White Polyurethane, Anti-Static, Non-Adhesive	■	■	■
	2-Ply Gray PVC Roughtop, Diamond Pattern	■	■	■
	2-Ply White Polyurethane, Anti-Static, Slightly Adhesive	■	■	■
	2-Ply Black Polyurethane X IMPG, Highly Conductive	■	■	■
	2-Ply Gray Polyurethane, X IMPG, Non-Adhesive	■	■	■
	2-Ply Black Polyurethane, Anti-Static, Non-Adhesive	■	■	■
T Slot	T Slots (Quantity)	1	2	2
Side Rails	Vertical Rails in 1-1/2"	■	■	■
	Vertical Rails in 1-1/2", Inc UHMW Lined	■	■	■
	Flared Rails at 45° in 1-1/2"	■	■	■
	Adjustable – Double and Single Bar	■	■	■
Standard Transfer		■	■	■
Tight Transfer		N/A	■	■
Supports	12" – 46" Height, Standard	12" – 46"H	12" – 46"H	12" – 46"H
Casters	3" Light Duty, 4" Heavy Duty Casters	■	■	■

Express program is after receipt of approved drawing. Changes may disqualify express shipment.

* Other speeds available through NLE sales.

■ = 5-Day

MOTOR / STARTER / CONTROL OPTIONS

BASIC AC DRIVE PACKAGE – NEMA1

MOTOR, A/C DRIVE ASSEMBLY W/4' CORD BETWEEN MOTOR AND CONTROL AND 10' CORD AND PLUG (EXCEPT 3PH NO PLUG)

HP	*Voltage	Phase	Hertz	**Turndown	24/48 HR	10 Day
1/3 HP	115/230/460	1, 3	60	1000:1	●	
1/3 HP	115/230/460	1, 3	60	20:1	■	
1/2 HP	115/230/460	1, 3	60	1000:1	●	
1/2 HP	115/230/460	1, 3	60	20:1	■	
3/4 HP	115/230/460	1, 3	60	1000:1	●	
3/4 HP	115/230/460	1, 3	60	20:1	■	
1 HP	115/230/460	1, 3	60	1000:1	●	
1 HP	115/230/460	1, 3	60	20:1	■	
1-1/2 HP	115/230/460	3	60	1000:1	●	
1-1/2 HP	115/230/460	3	60	20:1	■	
2 HP	230/460	3	60	20:1 / 1000:1	●	
3 HP	230/460	3	60	20:1 / 1000:1	●	
5 HP	230/460	3	60	20:1 / 1000:1	●	

NEMA 4/12 available in 10 Day. Add 24-hour for wiring and mounting.

* 115/230/1/60 Input – Converts to 230/3/60.

** Inverter Duty Rated Motor = 1000:1 Turndown; Premium E Motor = 20:1 Turndown (Max Speed/Turn Down = Min Speed).

STARTER PACKAGE – NEMA1

MOTOR WITH MAGNETIC FULL VOLTAGE NON-REVERSING/ REVERSING STARTER

HP MIN	HP MAX	Voltage	*Phase	Hertz	Type	24/48 HR	10 Day
1/4 HP	1 HP	115/230/460	1, 3	60	FVNR/REV	■	
1-1/2 HP	3 HP	230/460	3	60	FVNR/REV	■	●
5 HP	5 HP	230/460	3	60	FVNR/REV		●

NEMA 4/12 available in 10-Day. Add 24-hour for wiring and mounting.

Non-Reversing includes Start/Stop pushbuttons w/4' cord between motor and control and 10' cord and plug (3ph no plug).

Reversing includes Forward/Reverse/Stop pushbuttons w/4' cord between motor and control and 10' cord and plug (3ph no plug).

* 3 Phase includes a Control Power Transformer for stated voltage to 120V AC Control Power.

NON-REVERSING/REVERSING STARTER PACKAGE OPTIONS (PICK ONLY 1) – 10-DAY

Remote Start/Stop w/10' Cable
Foot Switch Fully Guarded Momentary w/10' Cable
Remote Forward/Reverse/Stop w/10' Cable
Foot Switch Fully Guarded Momentary or Maintained Forward/Reverse w/10' Cable
Remote E-Stop Push/Pull w/10' Cable
Cable Pull E-Stop for Reversing Starters w/Cable Kit (up to 50') and 10' Control Cable

OTHER CONTROL OPTIONS – 10 DAY

Photoelectric Sensor, (Diffuse/Retroreflective/Background Suppression/ Thru-Beam), 5 Wire AC/DC Supply, NC/NO Output, Sensing Distance 0-40M; Time Delay

Photoelectric Accessory – Reflector (50 X 50 mm)

Photoelectric Accessory – Mounting Bracket

Photoelectric Accessory – Thru-Beam Accessory

Disconnect Switch, NEMA 12 Enclosure (up to 25A) 1ph/3ph

AC Drive – Keypad IP 65 Remote w/Module and 8' Cord

MANUAL STARTER PACKAGE – NEMA1

MANUAL MOTOR STARTER W/OL PROTECTION INCLUDING START/STOP PUSHBUTTONS

HP MIN	HP MAX	Voltage	Phase	Hertz	24/48 HR	10 Day
1/4 HP	1 HP	115	1	60	■	

■ = 24-48 Hour

● = 10-Day



THE NEW LONDON DIFFERENCE

With 70 years of conveyor experience, we'll deliver valuable ideas and help you make decisions to quickly improve performance and your bottom line.

UNMATCHED SALES SUPPORT | COMPETITIVE PRICES | QUICK & ACCURATE QUOTES

Get up and running fast with one of the industry's most extensive quick shipment programs. Uptime Express™ offers a wide variety of conveyors that ship as quickly as 24 hours; maximum of 10 days. Over 29,000 sizes are available to ship in 24 hours.



1700 Division Street, New London, WI 54961
800.437.1994 | 920.982.4030
nlesales@nleco.com | nleco.com